PM560 SUPERCHARGE YOUR WAREHOUSE WITH THE ULTIMATE DATA-CAPTURE MACHINE

Next-generation technology inside the classic

While the PM560 is built into the same external form factor as its predecessor, the PM550, the technological enhancements are a leap into the future. The new handheld terminal is equipped with a faster, more efficient 2.0 GHz octa-core processor, coupled with 4 GB/ 64 GB storage, and it now operates on Android 11, a substantial upgrade from the PM550's Android 7. New advanced network features like Wi-Fi 6 and 2x2 MU-MIMO improve the user experience significantly with faster and more secure connections. While many have been changed, the identical form factor ensures backward compatibility, making the PM560 compatible with PM550 accessories including the Single Slot Cradle, 4-Slot Cradle, and 6-Slot Battery Charger. This compatibility ensures a seamless and low-cost transition to the PM560 with all the benefits of using the latest device.

Advanced features tailored for seamless warehouse operations

The BLE Beacon transmits location signals for as long as six months, even when the device is powered down or without the main battery, making asset management easier than ever. With the addition of the Enterprise Hot-Swap, the device's screen remains active during battery changes and initiates a countdown. This informs workers how much time is left before a device shutdown and ensures an uninterrupted workflow before, during, and after a battery swap. For accurate data input, the PM560 comes with two keypad options: Alphanumeric and numeric. These keys deliver tactile feedback, a feature that proves particularly valuable when wearing gloves. The PM560 has its removable 6,300 mAh battery inside the gun handle, retaining the renowned ergonomic weight distribution of PM550. The scan engine comes in three options to choose from according to your specific business needs, while all three read 1D/2D barcode symbologies.

Built to withstand extreme work environments

Engineered for heavy-duty environments, PM560 is a rugged handheld terminal that excels in industrial settings. This durable device has been tested against 1.8 m (6 ft.) drops onto concrete at room temperature and 1.5 m (5 ft.) across the operating temperature range. The IP65 rating affirms its dust and water resistance, ensuring a reliable operation even under severe conditions. The Gorilla Glass covering the screen gives an extra degree of protection against rough handling. Whether faced with repeated drops, dramatic temperature changes, or other extreme circumstances, the PM560 is built to endure.

Industries

Transport & Logistics Warehouse Management Manufacturing

Accessories

Standard

AC/DC Power Adaptor Country Plug USB-C Cable LCD Protection Film Battery: 6,300 mAh Hand Strap

Optional

Single Slot Cradle (opt. Ethernet) 4-Slot Cradle 6-Slot Battery Charger PM560 is backward compatible with PM550 charging cradles.

POINT Mobile



PM560

PERFORMANCE CHARACTERISTICS		
Operating system		
Google Android (GMS & AOSP)	Android 11 (upgradable to Android 14) FOTA (Firmware Over The Air) update	
Memory and stora	age	
RAM/ROM	4 GB/64 GB	
Sensor	Accelerometer	
PHYSICAL (CHARACTERISTICS	
Dimensions	204.5 mm x 79 mm x 175 mm 8.05 in x 3.11 in x 6.89 in	
Weight	602 g/21.2 oz.	
Display	4.3" IPS panel (480 x 800 pixels), WVGA LED backlight Daylight readable (450 nits) Multi-touch capacitive Corning Gorilla Glass	
Power		
Main battery Back-up battery	6,300 mAh, 3.63 V, Li-ion rechargeable 400 mAh, 3.8 V, for Enterprise Hot-Swap (UI Timer)	
Key and buttons		
Keypad Buttons	Alphanumeric, Numeric Power (left), Scan trigger (gun handle)	
Voice and audio	Microphone (front), built-in speaker (back)	
Standard communications	USB 2.0 Type-C POGO 14 pin on the bottom for charging	
Notification	LED on front/top (scanning), LED on rear/bottom (scanning), LEDs with dual color on touch panel (charging status, warning), Vibration, Beep	

Wireless LAN	
Radio	IEEE 802.11 a/b/g/n/ac/ax/d/h/i/k/r/v, 2x2 MU-MIMO
Data rates	5 GHz: 802.11 a/n/ac/ax up to 1200 Mbps 2.4 GHz: 802.11 b/g/n/ax up to 286.8 Mbp
Operating channels	1 to 13 (2412~2472 MHz) 36 to 165 (5180~5825 MHz)
Channel bandwidth	20, 40, 80 MHz
Security and encryption	WEP/WPA/WPA2 Personal (TKIP/AES), WPA/WPA2 Enterprise (TKIP/AES), WPA3 Personal (SAE), WPA3 Enterprise (AES), WPA3 Enterprise 192-bit mode (GCMP 256), Enhanced Open (OWE), PEAP (MSCHAPV2, GTC), TLS, TTLS (PAP, MSCHAP, MSCHAPV2, GTC), PWD, LEAP
Fast Roam	CCKM, 802.11r
Wireless PAN	
Bluetooth	Bluetooth Class I
Bidetootii	Ver. 5.0 BLE support
	Beacon (transmits signals for up to 6 month power-off and without main battery)
DATA CAPI	power-off and without main battery)
	power-off and without main battery)
Integrated scan e	power-off and without main battery)
Integrated scan e	power-off and without main battery)
Integrated scan of SE4750, N6703, I	power-off and without main battery) FURE engine options N6803 FR* all supporting 1D/2D barcode
Integrated scan of SE4750, N6703, I symbologies	power-off and without main battery) FURE angine options N6803 FR* all supporting 1D/2D barcode Communication) Reader for NFC Forum (Tag Types 1 to 5),
Integrated scan of SE4750, N6703, I symbologies	power-off and without main battery) FURE engine options N6803 FR* all supporting 1D/2D barcode Communication) Reader for NFC Forum (Tag Types 1 to 5), P2P Active (106 to 424 kbps) Initiator and Target, P2P Passive (106 to 424 kbps) Initiator and Target
Integrated scan of SE4750, N6703, I symbologies MFC (Near Field of NFC-Forum (NFC-IP Modes) Reader	TURE engine options N6803 FR* all supporting 1D/2D barcode Communication) Reader for NFC Forum (Tag Types 1 to 5), P2P Active (106 to 424 kbps) Initiator and Target, P2P Passive (106 to 424 kbps) Initiator and Target ISO/IEC 14443 A, ISO/IEC 14443 B, ISO/IE 15693, Mifare Classic 1K/4K, Mifare DESFire, Mifare UltraLight©, Sony FeliCa

Operating temperature	-20 °C to 60 °C/-4 °F to 140 °F
Storage temperature	-25 °C to 70 °C/-13 °F to 158 °F
Humidity	95% non-condensing
Drop	1.8 m (6 ft.) multiple drops to concrete at room temperature (23 °C/73° F)
	1.5m (5 ft.) multiple drops to concrete


across the operating temprature range, MIL-STD-810H

Tumble	500 cycles (1,000 hits), 1 m/3.3 ft. tumbles per IEC 60068-2-32 specification
Rain/dust proof (Sealing)	IP65
Electrostatic discharge	± 15 kV air discharge ± 8 kV contact discharge

REGULATORY APPROVALS AND COMPLIANCE

RCM, CE/CB, WPC, BIS, IC, FCC, NRCan, UKCA, IFITEL, NOM, SASO IECEE, CITC, TRA, NTRA, WEEE, REACH, RoHS, IMDA

ENTERPRISE SOLUTION



PMDM is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration that the workers can concentrate on their work with the device, and also decrease the device downtime by predicting when to replace the battery, etc.



The EmKit[™] is Point Mobile's value-added service kit engineered for the pure benefit of system integrators. EmKit supports the utilization, solution development, and secure management of your business devices.

PULS - ANDROID UPDATE & SECURITY

PULS is a Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.

PULS Patches, updates & Lifetime Support

Stay up-to-date with the latest updates for 7 years PULS comes free of charge for security patches & updates Get the latest Android version and its newest features Conveniently update your devices in the field by FOTA

For further information, please visit www.pointmobile.com or contact your regional sales representative.

WARRANTY

Subject to the Terms and Conditions. PM560 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please contact: service@pointmobile.com

*MOQ applies: Please contact sales representatives for more information.

Corporate Headquarters

Point Mobile Co., Ltd. pm_sales1@pointmobile.com +82 2 3397 7870

North America Point Mobile Americas LLC

info@pointmobileamericas.com +1 425 780 4452

Europe

Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

China

Point Mobile China info@pointmobile.com.cn +86 755 8869 1169

For more information, visit www.pointmobile.com

Google, Android, Google Play and other marks are trademarks of Google LLC. Copyright © 2006-2025 Point Mobile Co., Ltd. All rights reserved. Point Mobile Co., Ltd. is the designer and manufacturer of handheld mobile computers. The Point Mobile logo is a registered trademark and symbol of Point Mobile. Features and specifications are subject to change without prior notice.

