# POINT Mobile

를

# PM84

## **ELEVATE YOUR BUSINESS WITH A PRACTICAL** AND HIGH-QUALITY MOBILE COMPUTER

#### **Enterprise Mobile Device for All Business Sizes**

Meticulously designed, the PM84 stands out as a practical choice for businesses, yet delivers uncompromising performance. Powered by an octa-core processor and furnished with 4 GB RAM and 64 GB ROM standard storage, the device ensures a smooth user experience. A robust, easily replaceable 4,950 mAh (opt. 7,020 mAh) battery powers the device throughout the day. The back cover and the battery comprise one integrated part, contributing to increased safety and robustness, and offering a much easier on-the-spot battery replacement. PM84 features a 13 MP rear camera with Auto Focus for quick and clear on-site image capture, while 5 MP front camera facilitates video calls for clearer communication, especially when delivering real-time on-site information.

#### **Productivity-Enhancing Business Features**

Enjoy optimal user experience for your business with the PM84, certified by Android Enterprise Recommended. AER certified devices meet Google's strict requirements, including regular and consistent software and security updates. The unique Enterprise Hot-Swap feature saves time and safeguards your ongoing tasks, by allowing uninterrupted screen operation during battery replacement and initiating a safe shutdown countdown timer. Managing your devices has never been easier with Point Mobile Device Management (PMDM). It enables a remarkably straightforward and centralized process for the initial setup and updating of hundreds of devices. Furthermore, Point Mobile's extensive partnerships with third-party solution providers offer a variety of advanced MDM solutions from which you can choose to meet your specific business needs. The scan engine is optimized for fast and accurate data capture reading all commonly used 1D/2D symbologies, expanding the applicability of PM84 to various industries including retail, e-commerce, delivery services, transportation, and warehouse management.



Built to excel in demanding business environments, the PM84 boasts 1.8 m (6 ft.) drop resistance with the Rugged Boot and 1.5 m (5 ft.) without, onto granite and meets MIL-STD-810H drop standards. It passed a 500-cycle, 0.5 m (1.6 ft.) tumble test and operates within a temperature range of -20 °C to 60 °C (-4 °F to 140 °F), proving its suitability for even the harshest industrial settings. Equipped with Corning Gorilla Glass, the PM84 is designed for an extended lifecycle and exceptional durability.





#### **Industries**

Field Services **Transport & Logistics** Warehouse Management Retail Hospitality

#### Accessories

#### Standard

AC/DC Power Adaptor Country Plug LCD Protection Film USB-C Cable

Battery

- Standard: 4.950 mAh
- Extended: 7.020 mAh

Hand Strap

#### Optional

Single Slot Cradle (opt. Ethernet) 4 Slot Battery Charger Gun Handle LIHE REID Reader Rugged Boot





































#### **PM84**

#### PERFORMANCE CHARACTERISTICS

Main processor

Octa-core @ 2.0 GHz

Operating system

Google Android (GMS & AOSP)

Android 13 (upgradable to Android 15) FOTA (Firmware Over The Air) update

Memory and storage

RAM/ROM

4 GB / 64 GB micro SD

Supports up to 512 GB using ExFAT file system SIM 1 nano SIM

Proximity sensor, Light ambient sensor, Accelerometer, Gyro sensor, Digital

compass

PHYSICAL CHARACTERISTICS

164.8 x 78 x 17.6 mm Dimensions 6.5 x 3.1 x 0.7 in.

Weight 266 g / 9.4 oz

5.45" IPS panel (720 x 1440 pixels), HD+ Display

LED backlight

Daylight readable (440 nits, typical)

Wideviewing angle Multi-touch capacitive Corning Gorilla Glass

4,950 mAh, 3.87 V, Li-ion rechargeable 7,020 mAh, 3.87 V, Li-ion rechargeable 95 mAh, 3.7 V (10C), Enterprise Hot-Swap Standard battery Extended battery Back-up battery

Key & Buttons

Riaht Scan Scan, Volume Left Top Power

Voice & Audio **Dual microphones** 

Receiver

Speaker on front side (93 ± 3 dB)

Standard

USB 2.0 Type-C/OTG communications POGO 2 pin

POGO 5 pin in rear

Notification 2 x Dual LEDs for power (R/G) and

warning (R/B) indication

Vibration

#### **GLOBAL NAVIGATION SATELLITE SYSTEM**

WLAN SKII: No GNSS WWAN SKU: GNSS receiver support for GPS (A-GPS), GLONASS, Galileo, and Beidou

#### **WIRELESS**

Wireless WAN

EDGE/GPRS/GSM 900/1800/850/1900 WCDMA R1/2/4/5/6/8/19

LTE FDD B1/2/3/4/5/7/8/12/13/17/19/20/25/26/28

LTE TDD B38/39/40/41

Wireless LAN

Radio

IEEE 802.11 a/b/g/n/ac/d/h/i/k/r/v,

5 GHz: 802.11 a/n/ac: Up to 433 Mbps 2.4 GHz: 802.11 b/g/n: Up to 150 Mbps Data rates

Operating 1 to 13 (2412~2472 MHz) 36 to 165 (5180~5825 MHz) channels

Channel bandwidth 20, 40, 80 MHz

Security and encryption

WEP / WPA / WPA2 / WEP, RC4 Algorithm / TKIP, RC4 Algorithm / AES, Rijndael Algorithm, EAP-TLS / EAP-TTLS / PEAP-GTC /PEAP-MSCHAPv2 /LEAP supported, WiFi Direct and Hot spot support, WPA3 Personal WPA3 Enterprise, Enhanced Open

802.11r Fast Roam

Wireless PAN

Bluetooth Class I, ver. 5.1, BLE support

#### DATA CAPTURE

#### Integrated scan engine

Supporting 1D/2D barcode symbologies

Camera

13 MP, F. No. 1.8, Auto Focus Rear Front

5 MP

#### NFC (Near Field Communication)

NFC-Forum Reader for NFC Forum (Tag Types 1 to 5), (NFC-IP Modes)

P2P Active (106 to 424 kbps) Initiator and Target, P2P Passive (106 to 424 kbps)

Initiator and Target

Reader ISO/IEC 14443 A, ISO/IEC 14443 B, ISO/IEC (PCD - VCD)

15693, Mifare Classic 1K/4K, Mifare DESFire, Mifare UltraLight©, Sony FeliCa

#### **USER ENVIRONMENT**

Operating -20 °C to 60 °C

temperature -4 °F to 140 °F

Storage -25 °C to 70 °C -13 °F to 158 °F temperature

Humidity 95% non-condensing Drop

1.8 m (6 ft.) with Rugged Boot and 1.5 m (5 ft.) without, multiple drops to granite surface across the operating temperature range, MIL-STD-810H

Tumble

500 cycles, 0.5 m (1.6 ft.) tumbles per

IEC 60068-2-32 specification

Rain/dust proof (Sealing)

IP65 / IP67

Electrostatic discharge

± 15 kV air discharge ± 8 kV contact discharge

**REGULATORY APPROVALS AND** 

## COMPLIANCE

CB, CE, FCC, NRCan, RCM, KC, CU, FAC, FSS, CST, SASO IECEE (SIRC), BIS, WPC, IMDA, NBTC, MTC, ROHS, WEEE, REACH, ANATEL, NOM019, NOM208, NOM-211 Parts 1 & 2 (IFITEL), IFT012 SAR

#### **ENTERPRISE SOLUTION**



Simple yet powerful management solution

PMDM is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration that the workers can concentrate on their work with the device, and also decrease the device downtime by predicting when to replace the battery, etc.



The EmKit<sup>™</sup> is Point Mobile's value-added service kit engineered for the pure benefit of system integrators. EmKit supports the utilization, solution development, and secure management of your business devices

#### **PULS - ANDROID UPDATE & SECURITY**

PULS is a Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.



PULS

Patches, updates & Lifetime Support

Stay up-to-date with the latest security updates for up to 7 year Conveniently update your devices in the field by FOTA Update Android Versions and use new features via PULS\*

For further information, please visit www.pointmobile.com or contact your regional sales representative \*Android version updates may come with restrictions and could incur charges

#### WARRANTY

Subject to the Terms and Conditions, PM84 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please contact: service@pointmobile.com

Point Mobile Co., Ltd https://www.pointmobile.com/en/contactus +82 2 3397 7870

Point Mobile Americas LLC info@pointmobileamericas.com +1 425 780 4452

**Europe Headquarters** Point Mobile Europe GmbH info.pmeg@pointmobile.com +49 211 1588 5913

**China Headquarters** Point Mobile China info@pointmobile.com.cn +86 755 8869 1169