

# PM452

# NEXT GENERATION HANDHELD TERMINAL FOR THE STATE-OF-THE-ART SCANNING PERFORMANCE

# **Fine-Tuned for Maximum Data Capture Efficiency**

Introducing the PM452, a powerhouse in handheld terminal technology, meticulously engineered to deliver unparalleled scanning performance in any environment. With powerful scan engine options, including an extra-long-range and a flexible range scanner with dynamic reading capabilities, the PM452 provides fast and accurate reading of various symbologies. With a robust 2.2 GHz processor and ample 6 GB RAM / 128 GB flash memory, the device excels in processing data and decoding symbologies quickly, even in challenging conditions such as low lighting or damaged barcodes. The 13 MP camera on top of the device, equipped with PDAF (Phase Detection Auto Focus) technology, captures clear images in a split second.

## **Enhanced Connectivity for Seamless Operations**

The PM452 sets new standards in connectivity and efficiency with Wi-Fi 6E, enhancing data security, preserving battery life, and ensuring swift data transmission. Its advanced network capacity empowers businesses to effortlessly manage larger datasets, catalyzing productivity growth. With the LTE option, workers can utilize the device seamlessly throughout the entire supply chain, leading to uninterrupted operations. The optional 5,700 mAh extended battery gives users enough power to stay connected and productive all day, wherever they are.

#### **Choose Your Ideal Device**

Choose from a standard range 1D/2D imager or opt for the extra-long-range one that boasts an incredible reading distance of up to 29 m when reading certain types of symbologies. Tailor your PM452 further with three keypad options: numeric, function numeric, or alphanumeric. To enhance efficiency further, consider the optional ergonomically designed, detachable Gun Handle which boosts productivity in your workforce.

## **Pragmatic Device for Any Size of Business**

PM452 is well-equipped with the latest technologies, including Android 13, advanced scan engines, and Wi-Fi 6E, while remaining as a pragmatic choice for businesses of all sizes. Its exceptional durability keeps maintenance simple and downtime low. With IP65 water/dust resistance, a 2.0 m (6.6 ft.) drop resistance to concrete at room temperature, and an operating temperature ranging from -20 °C to 60 °C (-4 °F to 140 °F), the PM452 is well protected and suitable for any type of work setting.





#### Industries

Transport & Logistics
Manufacturing
Warehouse Management

#### Accessories

#### Standard

AC/DC Power Adaptor Country Plug LCD Protection Film

- Standard: 4,000 mAh
- Extended: 5,700 mAh

Stylus Wristband

#### Optional

Single Slot Cradle (opt. Ethernet)

- 4 Slot Cradle
- 4 Slot Battery Charger Gun Trigger





































# PM452

#### PERFORMANCE CHARACTERISTICS

Main processor

Octa-core @ 2.2 GHz

Operating system

Google Android (GMS & AOSP)

Android 13 (upgradable to Android 18)\* FOTA (Firmware Over The Air) update

Memory and storage

RAM / Flash micro SD

SIM

4 GB / 64 GB or 6 GB / 128 GB Supports up to 512 GB using ExFAT file system

1 micro SIM

Proximity sensor, Light ambient sensor, Accelerometer, Gyro sensor

PHYSICAL CHARACTERISTICS

Dimensions 214.9 x 77.3 x 39.3 mm 8.5 x 3.0 x 1.6 in.

450 a / 15 9 oz

Display

Weight

4.3", IPS panel (480 x 800 pixel), WVGA LED backlight Daylight readable (max. 500+ nits) Wideviewing angle

Multi-touch capacitive Corning Gorilla glass

Power

Standard battery Extended battery Back-up battery

4,000 mAh, 3.7 V, Li-ion rechargeable 5,700 mAh, 3.63 V, Li-ion rechargeable 60 mAh, 3.7 V (10C), Hot-Swap

Keypad

Three options Numeric, Function Numeric, Alpha numeric

Voice & Audio

Built-in microphone Dual speakers

Standard USB 2.0 Type-C/OTG

POGO 7 pin communications

Notification

LED on top: power (R/G), warning (R/B)

LED on side: scan status (R/B)

Vibration

#### **GLOBAL NAVIGATION SATELLITE SYSTEM**

WLAN SKU: No GNSS

WWAN SKU: GNSS receiver support for GPS (A-GPS). GLONASS, Galileo, and Beidou

**WIRELESS** 

Wireless WAN

EDGE/GPRS/GSM 900/1800/850/1900 WCDMA R1/2/4/5/6/8/19

B1/2/3/4/5/7/8/12/13/17/19/20/25/26/28 LTE FDD

LTE TDD B38/40/41

Wireless I AN

Data rates

IEEE 802.11 a/b/g/n/ac/ax/d/h/i/k/r/v, Radio Wi-Fi 6E, Wi-Fi Direct and Hot Spot support,

6 GHz: 802.11 ax: Up to 867 Mbps 5 GHz: 802.11 a/n/ac/ax: Up to 867 Mbps

2.4 GHz: 802.11 b/g/n/ax: Up to 143 Mbps

1 to 13 (2412~2472 MHz) Operating channels 36 to 165 (5180~5825 MHz) 1 to 233 (5955~7115 MHz)

Channel bandwidth

20, 40, 80, 160 MHz

Security and encryption

WEP / WPA / WPA2 / WEP, RC4 Algorithm / TKIP, RC4 Algorithm / AES, Rijndael Algorithm, EAP-FAST / EAP-TLS / EAP-TTLS / PEAP-GTC / PEAP-MSCHAPv2 / WPA3 Personal / WPA3 Enterpriase / Enhanced

Open (OWE)

802.11r

Wireless PAN

Fast Roam

Bluetooth Class I, ver. 5.2. BLE support

**DATA CAPTURE** 

Integrated scan engines

Three 1D/2D scan engine options including flexible range and

extra-long range

Camera

Top 13 MP, F. No. 2.0, PDAF (Phase Detection

Auto Focus), LED flash

NFC (Near Field Communication)

NFC-Forum (NFC-IP Modes)

Reader for NFC Forum (Tag Types 1 to 5)

Reader (PCD - VCD)

ISO/IEC 14443 A. ISO/IEC 14443 B. ISO/IEC 15693, Mifare Classic 1K/4K, Mifare DESFire, Mifare UltraLight©, Sony FeliCa

**USER ENVIRONMENT** 

-20 °C to 60 °C Operating temperature -4 °F to 140 °F

Storage

-40 °C to 70 °C

temperature

-40 °F to 158 °F

Humidity 95% non-condensing Drop 2.0 m (6.6 ft.) multiple drops to concrete

surface at room temperature

1.8 m (6 ft.) across the operating temperature range, MIL-STD-810H

Tumble

1,000 cycles (2,000 hits), 1.0 m (3.3 ft.)

per IEC 60068-2-31 specification

Rain/dust proof IP65

(sealing)

± 15 kV air discharge Electrostatio ± 8 kV contact discharge

discharge **REGULATORY APPROVALS AND** 

COMPLIANCE

CB, CE, RoHS, WEEE, FCC, IC, RCM, KC, NRCan, BIS, WPC, IMDA, NBTC, CITC, SIG

**ENTERPRISE SOLUTION** 

Simple yet powerful management solution

PMDM is a mobile device management solution for managing and monitoring your Point Mobile Android devices.

Centralized management of enterprise devices is vital for better productivity. You should provide a device configuration that the workers can concentrate on their work with the device, and also decrease the device downtime by predicting when to replace the battery, etc.

EmKit Enterprise Mobility Kit

The EmKit™ is Point Mobile's value-added service kit engineered for the pure benefit of system integrators. EmKit supports the utilization, solution development, and secure management of your business devices

**PULS - ANDROID UPDATE & SECURITY** 

PULS is a Point Mobile's lifetime solution, which extends the life cycle of Android-based Point Mobile enterprise devices to up to seven years after a product launch.



**PULS** 

Patches, updates & Lifetime Support

Stay up-to-date with the latest security updates for up to 7 year Conveniently update your devices in the field by FOTA Update Android Versions\*\* and use new features via PULS

For further information, please visit www.pointmobile.com or contact your regional sales representative.

WARRANTY

Subject to the Terms and Conditions, PM452 carries 1 (one) year-warranty period from the date of purchase against the defective materials and manufacturing defects.

For the further inquiry, please leave your message here: https://www.pointmobile.com/en/contactus.

The Android version may vary based on the mobile processor product roadmap. The upgradeable version is subject to change on the manufacturer's policy and condition.

\*\* Android version updates may come with restrictions and could incur charges.

Corporate Headquarters

Point Mobile Co., Ltd. https://www.pointmobile.com/en/contactus +82 2 3397 7870

NA Headquarters

Point Mobile Americas LLC info@pointmobileamericas.com +1 202 798 0786

**Europe Headquarters** Point Mobile Europe GmbH info.pmeg@pointmobile.com

+49 211 1588 5913

China Headquarters Point Mobile China info@pointmobile-cn.com +86 755 8869 1169